

1125



The Tally DASCOM 1125, is a 24 pin, 80 column serial dot matrix printer with USB, parallel and serial interfaces as standard. Compact in size, the 1125 is perfect for industrial environments and front and back office applications where space is limited.

With low running costs, high quality output and an easy to use control panel it's ideal for small business, low volume listings and reports, as well as dispatch notes and labels.

Compact in size and low on running costs

- Compact 24-pin narrow carriage printer
- Up to 375 characters per second
- Ideal for front and back office applications
- Auto switching USB, parallel and serial interface
- Long life ribbon
- Small footprint

In addition to these applications, the 1125 is also well suited to measurement and control systems.

Amongst the lowest priced matrix printers available today the 1125 also offers a long life ribbon giving this printer very low running costs.

For draft printing it's considerably less expensive running costs make it a viable alternative to low cost ink-jet printers.

Available Configuration:

1125 Standard Product

SERIAL MATRIX
PRINTERS

MOBILE
PRINTERS

THERMAL
PRINTERS

LINE MATRIX
PRINTERS

LASER
PRINTERS

CONNECTIVITY

CONSUMABLES

SERVICE

1125

Print Speed	10 cpi: 375cps (HSD), 250 cps (Draft), 83 cps (LQ) 12 cpi: 300 cps (Draft), 100 cps (LQ)
Print Method	Serial Impact Dot Matrix
Resolution	Up to 360 x 360 dpi
Throughput (ECMA 132)	295 pages per hour
Character Density	10, 12, 15, 17.1, 20cpi, Proportional Spacing
Line Density	1, 2, 3, 4, 6, 8 lpi
Printhead life	400 Million Strokes per pin
Memory	68 kB
Standard Connectivity	USB 2.0, parallel (Bi-directional) and Serial RS232
Standard Emulation	Epson LQ (ESC P/2), IBM ProPrinter (2390 Plus)
Fonts	Draft, Courier, Roman, Sans Serif, Prestige, Script, Orator, Gothic, Souvenir, OCR-A/B*, 10 Barcodes
Consumables	Black Ribbon: 7 million characters
Standard Paper Handling	Push tractor and single sheet tray
Number of Copies	Original +4 (5-part forms)
Paper Type	Continuous forms, cut sheet
Paper Weight	52-100 gsm
Paper Size	76,2 to 254 mm wide
Physical Weigth	5 kg
Physical Size	(HxWxD): 159x359x285
Power Voltage	230 V / 50 to 60 Hz
Power Consumption	max 3,8W in Stand by
Reliability MTBF	10.000 hours
Drivers	Windows 2000, 2003 Server, XP, Vista, Windows 7
Temperature	+5°C to +40°C
Humidity	10% to 80% (not condensing)
Acoustic	< 51dB(A) (ISO 7779)

Note NB: For OCR applications it is recommended that your readers are tested with print samples supplied by DASCOM prior to purchase. Paper is a highly variable medium and should be tested prior to purchase. The quoted consumable life is the average for the printer when used under normal operation conditions.

DASCOM Europe GmbH
Heuweg 3 • 89079 Ulm
Tel.: +49 731 2075-0 • Fax: +49 731 2075-563
info@dascom.com • www.dascom.com

SERIAL MATRIX PRINTERS
MOBILE PRINTERS
THERMAL PRINTERS
LINE MATRIX PRINTERS
LASER PRINTERS