

1225



Tally
DASCOM

The Tally Dascom 1225 is a 24 pin, 136 column serial dot matrix printer with USB and parallel interfaces as standard. The wide carriage printer is perfect for industrial environments and front and back office applications.

With low running costs, high quality output and an easy to use control panel it's ideal for low volume listing reports, invoices and other critical documents, as well as dispatch notes and labels.

Excellent performance and low running-costs

- Compact 24-pin wide carriage printer
- Up to 375 characters per second
- Ideal for front and back office applications
- Auto switching USB and parallel interface
- Long life ribbon

In addition to these applications, the 1225 is also well suited for measurement and control systems.

Amongst the lowest priced matrix printers available today the 1225 also offers a long life ribbon which means fewer ribbon changes, less downtime and lower running costs.

Available Configuration:

1225 Standard Product

SERIAL MATRIX
PRINTERS

MOBILE
PRINTERS

THERMAL
PRINTERS

LINE MATRIX
PRINTERS

LASER
PRINTERS

CONNECTIVITY

CONSUMABLES

SERVICE

1225

Print Speed	10 cpi: 375 cps (HSD), 250 cps (Draft), 83 cps (LQ) 12 cpi: 300 cps (Draft), 100 cps (LQ)
Print Method	Serial Impact Dot Matrix
Resolution	Up to 360 x 360 dpi
Throughput (ECMA 132)	336 pages per hour
Character Density	10, 12, 15, 17.1, 20cpi, Proportional Spacing
Line Density	1, 2, 3, 4, 6, 8 lpi
Printhead life	400 Million Strokes per pin
Memory	48 kB
Standard Connectivity	USB 2.0 and parallel (Bi-directional)
Standard Emulation	Epson LQ (ESC P/2), IBM ProPrinter (2390 Plus)
Fonts	Draft, Courier, Roman, Sans Serif, Prestige, Script, Orator, Gothic, Souvenir, OCR-A/B*, 10 Barcodes
Consumables	Black Ribbon: 7 million characters
Standard Paper Handling	Push tractor and single sheet tray
Number of Copies	Original +4 (5-part forms)
Paper Type	Continuous forms, cut sheet
Paper Weight	52-100 gsm
Paper Size	76,2 to 420 mm wide
Physical Weigth	8,5 kg
Physical Size	(HxWxD): 173x587x333 mm
Power Voltage	230 V / 50 to 60 Hz
Power Consumption	max 7,6 W in Stand by
Reliability MTBF	10.000 hours
Drivers	Windows 2000, 2003 Server, XP, Vista, Windows 7
Temperature	+5°C to +40°C
Humidity	10% to 80% (not condensing)
Acoustic	< 55dB(A) (ISO 7779)

Note NB: For OCR applications it is recommended that your readers are tested with print samples supplied by DASCOM prior to purchase. Paper is a highly variable medium and should be tested prior to purchase. The quoted consumable life is the average for the printer when used under normal operation conditions.

DASCOM Europe GmbH
Heuweg 3 • 89079 Ulm
Tel.: +49 731 2075-0 • Fax: +49 731 2075-563
info@dascom.com • www.dascom.com

SERIAL MATRIX PRINTERS
MOBILE PRINTERS
THERMAL PRINTERS
LINE MATRIX PRINTERS
LASER PRINTERS