

1430



Tally DASCOM's 1430 flat-bed serial dot matrix printer, is a 24 pin, 106 column printer with USB and parallel interfaces as standard. The printer is ideal for front office applications in retail outlets, travel agents, train stations and doctor's surgeries where a wide range of media is used.

With high quality output, an easy to use control panel and the option to use pre-cut or tractor fed paper, the 1430 is ideal for counter-top printing applications such as, tickets, receipts, forms and multi-part documents.

High speed and quality in wide format

- Wide carriage 24-pin flat-bed printer
- Print speeds up to 450 characters per second
- Ideal for front office applications
- Flexible media handling
- Auto switching USB and parallel interface
- Long life ribbon

The long life ribbon of the 1430 means fewer ribbon changes, less downtime and lower running costs.

With print speeds of 450 characters per second (cps) and flexible media handling it keeps transactions smooth and the user happy.

The 1430 is a reliable and easy to use printer, with low running costs and flexible paper management.

Available Configuration:

1430 Standard Product

SERIAL MATRIX
PRINTERS

MOBILE
PRINTERS

THERMAL
PRINTERS

LINE MATRIX
PRINTERS

LASER
PRINTERS

CONNECTIVITY

CONSUMABLES

SERVICE

1430

Print Speed	10 cpi: 450 cps (HSD), 300 cps (Draft), 100 cps (LQ) 12 cpi: 360 cps (Draft), 120 cps (LQ)
Print Method	Flat Bed Serial Impact Dot Matrix
Resolution	Up to 360 x 360 dpi
Throughput (ECMA 132)	317 pages per hour
Character Density	10, 12, 15, 17.1, 20cpi, Proportional Spacing
Line Density	1, 2, 3, 4, 6, 8 lpi
Printhead life	400 Million Strokes per pin
Memory	68 kB
Standard Connectivity	USB 2.0 and parallel (Bi-directional)
Standard Emulation	Epson LQ (ESC P/2), IBM ProPrinter (2390 Plus)
Fonts	Draft, Courier, Roman, Sans Serif, Prestige, Script, Orator, Gothic, Souvenir, OCR-A/B*, 10 Barcodes
Consumables	Black Ribbon: 7 million characters
Standard Paper Handling	Friction and push tractor
Number of Copies	Original +7 (8-part forms)
Paper Type	Cut sheet , continuous forms
Paper Weight	52–157 gsm
Paper Size	51 to 304,8 mm wide
Physical Weigth	7,5 kg
Physical Size	(HxWxD): 202x495x342
Power Voltage	230 V / 50 to 60 Hz
Power Consumption	max 3,5 W in Stand by
Reliability MTBF	10.000 hours
Drivers	Windows 2000, 2003 Server, XP, Vista, Windows 7
Temperature	+5°C to +35°C
Humidity	10% to 80% (not condensing)
Acoustic	< 55 dB(A) (ISO 7779)

Note NB: For OCR applications it is recommended that your readers are tested with print samples supplied by DASCOM prior to purchase. Paper is a highly variable medium and should be tested prior to purchase. The quoted consumable life is the average for the printer when used under normal operation conditions.

DASCOM Europe GmbH
Heuweg 3 • 89079 Ulm
Tel.: +49 731 2075-0 • Fax: +49 731 2075-563
info@dascom.com • www.dascom.com

SERIAL MATRIX PRINTERS
MOBILE PRINTERS
THERMAL PRINTERS
LINE MATRIX PRINTERS
LASER PRINTERS